Fire Rated Meter Over Box

(Two Part Frame Type)



Key Features


- Fire rated 120 minutes
- Pre-punched fixing holes for simple installation
- Factory fitted Intumescent seal
- Air tight Neoprene seal
- Unique quick fitting hinge
- Secure steel construction
- Up to 2250 x 822 x 250mm sizes possible

The **Fire Rated Meter Over Box** is a **retrofit solution** for keeping your gas and electrical meters well protected. Independently tested by a **UKAS accredited laboratory** the **Fire Rated Meter Over Box** achieves a **120 minute integrity fire rating. Intumescent seal factory fitted** to the rear of the panel ensures that in the case of a fire, gaps are closed and the **fire is contained**.

The box is **easy to fit** and the fixing holes are concealed within the rear of the box to avoid any unsightly fixing points. Manufactured from **durable steel** the Meter Over Box will **protect meters** from **vandalism in communal spaces**.

Meter Over Boxes are fitted with a **3-point lock** as standard to ensure the security of the contents. Other locking options are available upon request. With our **made to measure service** we ensure the right fit for your project.

We manufacture the Meter Over Box to fit over your aperture or existing meter box.



Contact us for a factory tour or to arrange an on site demonstration





Fire Rated Meter Over Box (Two Part Frame Type)







Door Tray & Frame

Formed from 1.0 and 1.2mm Zintec electro-galvanised mild steel. Powder coated white RAL 9010 as standard. Other RAL colours available on request.

Hinge & Lock Mechanism

Removable pivot hinge system for quick door release. Square drive operated lock with **3-Point Locking Mechanism** and **Spring Loaded Invisible Keyhole (SLIK) system**.

Fire Rating

Available with **up to 120 minute** fire rating, testing undertaken independently by **UKAS** laboratory to **EN 1634-1:2014 + A1:2018**. Certification available upon request.

Smoke Tested

Neoprene seal is fitted to the door tray to minimise airflow.

Fitting

The **Fire Rated Meter Over Box** is secured to the wall using **80mm** long masonry fixings and rawl plugs suitable for the wall construction in the pre-punched fixing holes.

Operation & Maintenance

Using the **Square Drive 'T'-Key** supplied, engage the key into the lock and open or close the door. Three point locking rods engage into the head and threshold of the frame.

Avoid **abrasive cleaning materials**. Check the operation annually, especially the hinge points and lock, or more frequently if used very regularly. Tighten or oil as required.

Availability

Fire Rated Meter Over Boxes are made to order. Bespoke sizes available. Please call our **Technical Sales Team** to confirm stock and availability.

Online Support

See website for **fitting guides** and **videos**. **DXF**, **DWG**, **CAD**, **PDF**, **BIM cross-section drawings** and full technical specifications.

Contact us for a factory tour or to arrange an on site demonstration

